



# TL90 STANDARD LED

EFFICIENCY REDESIGNED



# STANDARD SPECIFICATION

ENGINE TYPE	Kubota Z482 2cyl Water Cooled 3.6kW @ 1500rpm diesel with electronic governor
HYDRAULIC SYSTEM	Bio-degradable Oil
FUEL CONSUMPTION	0.65 l/hr (Lamps only)
RUNNING TIME	177 Hours
LAMP SPECIFICATION	4 x 300W LED
AVERAGE SOUND PRESSURE LEVEL @ 7 METRES	61.5dB(A)
ALTERNATOR	Mecc Alte LT3 4 Pole, 230V, 50Hz
CONTINUOUS POWER / STANDBY POWER	2.5W / 2.8kW
POWER OUTLET SOCKETS	1 x 230Volt 16Amp
MAST MAXIMUM HEIGHT	8500mm*
MAST RAISE / LOWER TIME	12 / 18 secs
WIND SPEED	Up to 100km/h
STABILISERS	4 with 2 x rear heavy duty square wind down legs
BUNDING	Fully banded all fluids
ROAD LIGHTS AND REFLECTORS	Standard
DIMENSIONS FOR TRANSPORT (LxWxH)	2570mm x 1350mm x 2280mm
DIMENSIONS FULLY DEPLOYED (LxWxH)	2870mm x 2639mm x 8500mm*
WEIGHT FULLY FUELLED / UNFUELLED	956kg / 863kg
STANDARD SAFETY SYSTEM	Standard
QR CODES	Standard
VISUAL LEVEL GAUGES	Standard

\*When fitted with 9 section mast. Standard height 8010mm

## Standard Safety System Includes

- Automatic mast descent
- Emergency stop button
- Auto shutdown

## Features:



Super silent operation



TEN UNITS  
per truck



355° mast rotation